

Isolated converter

3105

- Isolation and conversion of standard DC signals
- Slimline housing of 6 mm
- Response time <7 ms
- Low cost
- DIP-switch configured




Application

- Isolation and conversion of standard DC signals.
- Galvanic separation of analog current and voltage signals.
- Elimination of ground loops and measurement of floating signals.
- A competitive choice in terms of both price and technology for galvanic isolation of current and voltage signals to SCADA systems or PLC equipment.
- Suitable for environments with high vibration stress, e.g. ships.

Technical characteristics

- Easy configuration via DIP-switches.
- The input is protected against overvoltage and polarity error.
- Factory-calibrated measurement ranges.
- Inputs and outputs are floating and galvanically separated.

Connections



Order:

Type
3105

Environmental Conditions

Specifications range.....	0°C to +70°C
Storage temperature.....	-40°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20
Installation in.....	Pollution degree 2 & measurement / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD).....	113 x 6.1 x 115 mm
Weight approx.....	70 g
DIN rail type.....	DIN EN 60715/35 mm
Wire size.....	0.13 x 2.5 mm ² / AWG 26...12 stranded wire
Screw terminal torque.....	0.5 Nm
Vibration: 2...25 Hz.....	±1.6 mm
Vibration: 25...100 Hz.....	±4 g

Common specifications

Supply

Supply voltage.....	16.8...31.2 VDC
---------------------	-----------------

Isolation voltage

Test voltage.....	2.5 kVAC
Working voltage.....	300 VAC

Response time

Response time (0...90%, 100...10%).....	< 7 ms
Max. power consumption.....	0.8 W
Internal consumption.....	0.4 W (typ.) / 0.65 W (max.)
Signal / noise ratio.....	> 60 dB
Accuracy.....	Better than 0.2% of selected range
Temperature coefficient.....	< ±0.015% of span / °C
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR NE 21, A criterion, burst.....	< ±1% of span

Input specifications

Current input

Measurement range.....	0...20.5 mA
Functional range.....	0...23 mA
Programmable measurement ranges.....	0...20 and 4...20 mA
Input voltage drop.....	< 1.5 VDC

Voltage input

Measurement range.....	0...10.25 V
Functional range.....	0...11.5 V / 0...5.75 V
Programmable measurement ranges.....	0/1...5 and 0/2...10 V
Input resistance.....	≥ 500 kΩ

Output specifications

Current output

Signal range.....	0...20.5 mA (span)
Programmable signal ranges.....	0 / 4...20 mA
Load (max.).....	23 mA/600 Ω
Load stability.....	≤0.01% of span / 100 Ω
Current limit.....	≤ 28 mA

Voltage output

Signal range.....	0...10 VDC
Programmable signal ranges.....	0/1...5 and 0/2...10 V
Load (min.).....	> 10 kΩ

*of span..... = of the DIP-switch selected output range

Approvals

EMC.....	2004/108/EC
LVD.....	2006/95/EC
EAC.....	TR-CU 020/2011
DNV Marine.....	Stand. f. Certific. No. 2.4
GL.....	V1-7-2
UL.....	UL 508